CB22 & CB25



Beckett's family of large condensate pumps are ideal for higher volume standard condensate removal application. Each pump operates quietly, efficiently and offers such features as a built-in safety switch and a one gallon tank. All pumps are UL/CUL listed.

Model #	Н	W	ι	Outlet	Inlet	Volts	Amps	Watts	Gallons per hour @ 60Hz / Rated Voltage				Safety	Check		Shut Off (Ft.)	
									1′	5′	10'	20'	Switch	Valve	w/Plug		Lb. Each
CB221UL	9 1/4"	6"	12"	3/8" O.D.	1.1"	115	1.5	120	108	90	70	19	√	√	√	22'	6.5
CB251UL	10 1/8"	6"	12"	3/8" O.D.	1.1"	115	1.3	106	108	100	84	40	√	√		25′	8.6
CB251ULHT	10 1/8"	6"	12"	3/8" O.D.	1.1"	115	1.3	106	108	100	84	40	√	V		25′	8.6
CB252UL	10 1/8"	6"	12"	3/8" O.D.	1.1"	230	0.9	125	108	100	84	40	√	√		25′	8.6
CB252ULHT	10 1/8"	6"	12"	3/8" O.D.	1.1"	230	0.9	125	108	100	84	40	√	√		25′	8.6

Beckett Automatic Condensate Units Coding Legend:

1- 115V 2- 230V

HT- High Temperature Unit 190°F Max. Water Temp.



CB22

Tank Capacity:

CB22 & CB25, 1 US gallon (3.785 Liters)



CB25

Average Performance